Allegan™ | RENO 600

Tile Makeover Kit



Don't Hack, Paint Your Tiles!

The 1st #GreenEpoxy in Asia

The Allegan Tile Makeover Kit is a breakthrough innovation in the field of home renovation. It offers a safe, cost-effective and sustainable alternative to replacing tiles entirely, saving you time, money, and unnecessary waste. This cutting-edge coating is formulated using HYDROSYNTHESIS™ technology making it a green and safer choice for conscious homeowners.



Allegan Features

- ✓ Water & Mould Resistant
- ✓ Low VOC & Low Odour
- ✓ 1 coat application

- ✓ 1K, No Hardener, No Mixing
- ✓ Full curing within 1 day
- ✓ Solves tiles leakage issue

All It Takes is 1 COAT to Transform Your Space

1 hour | Surface Prep 1 hour | Reno Coat 4 hours or overnight | Curing time Start using as usual!

2 ONE coat of RENO 600

READY!

Ideal surface: All types of tiles including Ceramic, Porcelain, and even natural stone. PLUS POINT, you can also use Allegan Tile for your countertops, furniture and other rigid surfaces!

What's in the kit



Allegan™ | RENO 600 Tile Makeover Kit

Technical Details

Usage	This kit has been especially developed for use on bathroom floor and generic wall tiles (including porcelain, ceramic & glass). Can be used on most substrates for interior and exterior including cementitious floor etc. *As it is difficult to cover all available substrates in our testing, it is recommended for our users to test the compatibility of this product on a small area prior to large scale application.
Coverage	One kit will cover 2.5m ²
Kit Content	One paint tray, 2 paint rollers, 1 paint handle, 1 sanding block, 1 tin of ALLEGAN RENO 600 Tile Paint
Number of Coats	One unless covering a dark coloured or heavily patterned tile or porous grouts.
Drying Time	Touch Dry within 30 minutes, paint over in 4 hours (usually not required), up to 12 hours full dry depending on temperature and humidity.
Ready for use	4 to 12 hours after application
Colours	12 colours & 1 clear coat
Finish	Glossy
Durability	Water and Mould Resistant
VOC	Ultra low VOC, Green Label Compliant
Storage	Keep in dry place away from direct sunlight. Storage temperature $4^{\circ}\text{C}-25^{\circ}\text{C}$ Shelf life is 12 months from the date of manufacture when stored as directed.

For interior & exterior application | Abrasion Resistant | Non Yellowing | Safe & Green Formulation

HYDROSYNTHESIS™ Technology



ALLE products undergo HYDROSYNTHESIS™ by harnessing the natural energy of water, be it in the form of atmospheric moisture or liquid, to form permanent chemical bonds. As a result, ALLE products are versatile in different application temperatures, humidity, and conditions.

Products which cure via HYDROSYNTHESIS™ are safe as they do not utilize hazardous chemicals, nor do they release any harmful chemicals to the environment.