

# Signature Series— ZeroSightline-HT

## Product Data

### Description

**AAMA Category** – Architectural

**AAMA Designation** – AW-110

**Configuration** – Outward Projected /  
Outswing Casement

**Series** – Zerosightline-HT

### AAMA Air, Water and Structural Testing

**Test Size** – AAMA 101 for Designation  
and/or Configuration

**Allowable Air** – Max 0.10 CFM/LF @ 6.24 PSF

**Uniform Load Deflection** – 110 PSF

**Water** – 15 PSF

**Uniform Load Structural** –165 PSF

### CRF and 'U' Value

**CRF** – CRF 65 – 75

**U-Value** – U 0.29 – 0.58

### Construction

**Minimum Wall Thickness** – 0.094"

**Minimum Wall Thickness @ Fasteners** – 0.094"

**Depth** – 3-3/4"

**Design** – Flat Back & Glazed-In

**Fabrication** – Mitered, Sealed, & Crimped  
w/Aluminum Corner Blocks

### Thermal Barrier

**Separation** – 1-1/8"

**Design** – Two Crimped In Place,  
Glass Reinforced Polyamide 6/6 Strips

### Weather-Stripping

**Primary Operable** – Two Rows EPDM

### Glazing

**Location** – Factory or Field

**Method** – Structural Silicone

### Screens

**As Specified** – Flat or Wicket

### Hardware

**As Specified** – Manufacturers Standard

### Finish

**As Specified** – Anodized or Painted

### Warranty

**As Specified** – 2, 5 or 10 Years (2 Year Standard)