

Klar Coat and Wicked White Coatings

Single coat, self-priming antimicrobial coatings offer the leading combination of quality, coverage and value.

Benefits

Antimicrobial ingredients inhibit growth of microorganisms on the dry coating surface.

Dries faster, re-coats without wait, applies in a single coat and self-priming. Higher percentage of volume solids ensures highest coverage rates.

Tintable, water-reducible acrylic formulation is ideal for post-remedial, existing- and new-construction.

Low VOC, Hazardous Air Pollutant (HAP) free product made in strict ISO 9001 QMS Standards facility comply with LEED EQ Credit 4.2.

Available in clear and brilliant white.



Dries Clear



Dries White

CAS No	CHEMICAL INGREDIENTS
71-63-3	n-Butyl alcohol
111-76-2	Butyl Cellosolve
25265-77-4	Texanol
5131-66-8	Butyl-Propanol

FROM THE MAKERS OF MMR



Use Instructions: For Interior Use Only.

1. Clean and dry surface (30-60% RH) or sand surfaces before application.
2. Cover to protect all "non-treatable" surfaces from overspray.
3. Use OSHA recommended personal protective equipment (PPE) per the SDS.
4. Mix with powered mixing device and mixing paddle.
5. Apply product via roller or airless spray system (1/2 horsepower or greater; using a 113 through 615 size reversible tip). Apply approximately 12 inches from the surface area.
6. To ensure complete and consistent coverage of product, a 4-7 wet film thickness that will cure 1.5-2.0 mils in dry film thickness.
7. Allow 7-15 minutes quick dry, 1-2 hours "dry-to-touch and overnight for full dry results.
8. Clean excess product from roller or airless spray system with warm water.

Clean up: Use clean, fresh water to clean equipment before product dries. Dispose of waste according to all existing local, state and federal regulations.

Bad Axe Mold Resistant Coating

10-Year Limited Warranty Bad Axe Restoration Products, Inc. warrants the performance of the Bad Axe coating line, against visible growth of mold and mildew for a period of ten years. The warranty is available to all residential owners or commercial contractors where application guidelines have been followed. The products must be applied on properly treated substrate(s) at a given spread rate of 300 sq. feet per gallon for qualification. Substrate must be cleaned and disinfected prior to applying Bad Axe coating.

A qualifying claim will allow for product replacement of non-conforming material or Bad Axe's option of refunding the original cost of the affected coating. The warranty will not cover the labor cost affiliated with the application of the products nor will it involve the labor associated with the correction of the affected areas.

Qualifications for the Limited Warranty

The substrate on which the Bad Axe coating is to be applied must be dry, clean, and free from mold and mildew growth. If mold/mildew is present prior to application, it must be removed and substrate cleaned and disinfected. A coating application rate of 300 sq. feet per gallon must be applied as well as conforming with all other application guidelines.

Warranty Disclaimers

Liability for consequential damages is specifically excluded. No other warranties expressed or implied are given.

Physical and Chemical Properties

	Klar Coat	Wicked White
Description	Paint, Non-Hazardous Liquid	
Physical State	Liquid	
Class	Class 55	
Vapor Density	Heavier than Air	
Readiness	Ready-To-Use	
pH	7.2 to 9.5	
Appearance	White, Dries Clear	White
Viscosity	Thick	
VOC sans water	.72 LB/GL	1.23 LB/GL
VOC as supplied	.35 LB/GL	.64 LB/GL
Solubility	Soluble in water	
Weigh @ LBS/GLt	9.87	11.54
Prep	Shake before use	
Odor	Mild	

Exclusions

The Limited Warranty does not cover, and Bad Axe Restoration Products will not be liable for the damage associated with the following;

1. Natural disasters and acts of nature; floods, hurricanes, tornadoes, hail, fire, earthquakes, windstorms, and lightning.
2. Substrate deterioration which impacts the integrity of the coating.
3. Improper application of the coating whether it be in surface preparation, surface treatment, or within a failure to apply the proper amount of coating material.
4. Product alterations and surface alterations. The coating can not be thinned for the Limited Warranty to apply. The substrate cannot be altered with paint.
5. Coating alterations or damaged caused by vandalism or another third party, or by the owner.
6. Damage resulting in water damage from ruptured pipes or any other source of water exposure.
7. Cracks, breaks, and openings within the substrate where the coatings are applied.

Warranty Claims

The following limited warranty applies to the Bad Axe Klar Coat and Bad Axe Wicked White. Bad Axe Restoration Products Inc. provides a 10-year limited warranty on the Bad Axe coating line of products. Bad Axe Restoration Products Inc. these products to perform satisfactorily when used in accordance with label directions. Bad Axe Restoration Products Inc. will replace the product or refund the purchase price in the event the product is proven defective, which shall be the exclusive remedy under the warranty.



Call Today 815-277-5100

www.BadAxeProducts.com

BAD AXE
RESTORATION PRODUCTS